

Printing date 12.08.2020 Version number 3 Revision: 12.08.2020

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Thermosoft Lacquer
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture

Light polymerising resin lacquer for the lacquering of soft and hard earmoulds of the Fotoplastand Otoacryltechnique.

- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Dreve Otoplastik GmbH Max-Planck-Straße 31 59423 Unna / Germany Tel.: ++49 2303 / 8807-0

Fax.: ++49 2303 / 8807-29

· Further information obtainable from:

Department Research & Development

Fax: ++49 2303 / 8807-562

Email: sicherheitsdatenblatt@dreve.de
• 1.4 Emergency telephone number:

Tel.: ++ 49 211 / 797-3350 Plant Fire Department Henkel

#### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

· Signal word Danger

(Contd. on page 2)



Printing date 12.08.2020 Version number 3 Revision: 12.08.2020

Trade name: Thermosoft Lacquer

(Contd. of page 1)

#### · Hazard-determining components of labelling:

methyl methacrylate ethyl methacrylate 2-ethylhexyl acrylate

2-hydroxyethyl methacrylate

Diphenyl(2,4,6-trimethylbenzoyl)phosphinoxide

2-Propenoic acid, reaction product with Pentaerythrite

#### · Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

#### · Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse

skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

#### · 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

### **SECTION 3: Composition/information on ingredients**

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:					
CAS: 80-62-6	methyl methacrylate				
EINECS: 201-297-1	♦ Flam. Liq. 2, H225; ♦ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335				
CAS: 97-63-2	ethyl methacrylate	10-25%			
EINECS: 202-597-5	Flam. Liq. 2, H225; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	-			
CAS: 103-11-7	2-ethylhexyl acrylate	2.5-10%			
EINECS: 203-080-7	① Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335				
CAS: 868-77-9	2-hydroxyethyl methacrylate	2.5-10%			
EINECS: 212-782-2	♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	-			
	Acrylic resin	≤2.5%			
	♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335				
CAS: 75980-60-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphinoxide	≤2.5%			
EINECS: 278-355-8	Repr. 2, H361f;  Aquatic Chronic 2, H411;  Skin Sens. 1, H317				
CAS: 1245638-61-2	2-Propenoic acid, reaction product with Pentaerythrite	≤2.5%			
EC number: 629-850-6	Eye Dam. 1, H318; 4 Aquatic Chronic 2, H411; 4 Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317				

(Contd. on page 3)



Printing date 12.08.2020 Version number 3 Revision: 12.08.2020

Trade name: Thermosoft Lacquer

(Contd. of page 2)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Do not induce vomiting.

Call a doctor immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

## **SECTION 6: Accidental release measures**

· 6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

GE



Printing date 12.08.2020 Version number 3 Revision: 12.08.2020

Trade name: Thermosoft Lacquer

(Contd. of page 3)

### **SECTION 7: Handling and storage**

## · 7.1 Precautions for safe handling

Avoid contact with skin and eyes.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

### · Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Protect from heat and direct sunlight.

Store in a cool location.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s) No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

## · Ingredients with limit values that require monitoring at the workplace:

#### 80-62-6 methyl methacrylate

WEL Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

Protective gloves should be changed regularly, especially after intensive contact with the product. For every workplace a suitable type of protective gloves must be selected.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

#### · Material of gloves

Butyl rubber, BR

As there are many different conditions in every day work these indications can only serve as an aid to orientation for the selection of suitable gloves for the handling of chemical products. By no means they can replace qualifying examinations by the end-user.

(Contd. on page 5)



Printing date 12.08.2020 Version number 3 Revision: 12.08.2020

Trade name: Thermosoft Lacquer

(Contd. of page 4)

These recommendations only apply to the product mentioned in the safety data sheet. When mixing with other substances or under conditions deviant from norm EN 374 a manufacturer of CE-approved gloves should be referred to.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

### **SECTION 9: Physical and chemical properties**

<ul> <li>9.1 Information on basic physical and chemical proper</li> </ul>	rties	prop	emical	ch	and	/sical	phy	basic	on	ation	Informa	. 9.1
---	-------	------	--------	----	-----	--------	-----	-------	----	-------	---------	-------

· General Information

· Appearance: Form:

Colour:

· Odour:

Odour threshold: Not determined.
 pH-value: Not determined.
 Change in condition
 Melting point/freezing point: Undetermined.
 Initial boiling point and boiling range: 101 °C
 Flash point: 10 °C
 Flammability (solid, gas): Not applicable.
 Ignition temperature: 245 °C
 Decomposition temperature: Not determined.

Fluid

Colourless

Characteristic

Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

· Auto-ignition temperature:

Lower: 1.8 Vol %
Upper: 12.5 Vol %
Oxidising properties Not determined
Not applicable.

· Vapour pressure at 20 °C: 47 hPa

· Density at 20 °C: 1.0 g/cm<sup>3</sup>

(Contd. on page 6)



Printing date 12.08.2020 Version number 3 Revision: 12.08.2020

Trade name: Thermosoft Lacquer

	(Contd. of page 5)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Solids content:	0.0 %
· 9.2 Other information	No further relevant information available.

### **SECTION 10: Stability and reactivity**

- 10.1 Reactivity No dangerous reactions if used according to specifications.
- 10.2 Chemical stability Stable if used according to specifications.
- · Thermal decomposition / conditions to be avoided:

Protect from heat and direct sunlight.

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

GB



Printing date 12.08.2020 Version number 3 Revision: 12.08.2020

Trade name: Thermosoft Lacquer

(Contd. of page 6)

## **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· European waste catalogue				
HP3	Flammable			
HP4	Irritant - skin irritation and eye damage			
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity			
HP13	Sensitising			

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information		
· 14.1 UN-Number · ADR, IMDG, IATA	UN1247	
· 14.2 UN proper shipping name · ADR	1247 METHYL METHACRYLATE MONOMER, STABILIZED solution 1247 METHYLMETHACRYLAT, MONOMER,	
· IMDG, IATA	STABILISIERT, LÖSUNG METHYL METHACRYLATE MONOMER, STABILIZED solution	
	(Contd. on page 8)	

- GE



Printing date 12.08.2020 Version number 3 Revision: 12.08.2020

Trade name: Thermosoft Lacquer

Trade name: Thermoson Lacquer	
	(Contd. of page 7)
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
· Class · Label	3 Flammable liquids.
· 14.4 Packing group · ADR, IMDG, IATA	II
<ul> <li>14.5 Environmental hazards:</li> <li>Marine pollutant:</li> </ul>	No
<ul> <li>14.6 Special precautions for user</li> <li>Danger code (Kemler):</li> <li>EMS Number:</li> <li>Stowage Category</li> <li>Stowage Code</li> </ul>	Warning: Flammable liquids. 33 F-E,S-E B SW2 Clear of living quarters.
14.7 Transport in bulk according to Annex of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
<ul><li>ADR</li><li>Limited quantities (LQ)</li><li>Excepted quantities (EQ)</li></ul>	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
<ul><li>Transport category</li><li>Tunnel restriction code</li></ul>	2 D/E
IMDG     Limited quantities (LQ)     Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1247 METHYL METHACRYLATE MONOMER, STABILIZED SOLUTION, 3, II

## **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

(Contd. on page 9)



Printing date 12.08.2020 Version number 3 Revision: 12.08.2020

Trade name: Thermosoft Lacquer

(Contd. of page 8)

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H225 Highly flammable liquid and vapour.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H361f Suspected of damaging fertility.
- H411 Toxic to aquatic life with long lasting effects.
- · Department issuing SDS: Department Research & Development
- · Contact: Dr. Thomas Veit, Lothar Sutor, Susanne Weber
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 4: Acute toxicity - oral – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

\* Data compared to the previous version altered.

GB