

Printing date 24.11.2020 Version number 5 Revision: 24.11.2020

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: FotoTec DLP.flex 70 Shore
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture

Material based on methacrylate resin for manufacturing of earmoulds and shells

- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Dreve Otoplastik GmbH Max-Planck-Straße 31 59423 Unna / Germany Tel.: ++49 2303 / 8807-0 Fax.: ++49 2303 / 8807-29

· Further information obtainable from:

Department Research & Development

Fax: ++49 2303 / 8807-562

Email: sicherheitsdatenblatt@dreve.de

• 1.4 Emergency telephone number:

Tel.: ++ 49 211 / 797-3350 Plant Fire Department Henkel

#### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms







GHS07 GHS08 GHS09

(Contd. on page 2)



Printing date 24.11.2020 Version number 5 Revision: 24.11.2020

Trade name: FotoTec DLP.flex 70 Shore

(Contd. of page 1)

· Signal word Warning

#### · Hazard-determining components of labelling:

Aliphatic difunctional Urethane Acrylate

2-phenoxyethyl methacrylate

(5-ethyl-1,3-dioxan-5-yl)methyl acrylate

Diphenyl(2,4,6-trimethylbenzoyl)phosphinoxide

#### · Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H361d Suspected of damaging the unborn child.

H411 Toxic to aquatic life with long lasting effects.

### · Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

#### · 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

## **SECTION 3: Composition/information on ingredients**

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
	Aliphatic difunctional Urethane Acrylate	
	♦ Skin Sens. 1, H317	
CAS: 66492-51-1	(5-ethyl-1,3-dioxan-5-yl)methyl acrylate	10-25%
EINECS: 266-380-7	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	
CAS: 10595-06-9	2-phenoxyethyl methacrylate	10-25%
EINECS: 234-201-1	Repr. 2, H361d;  Aquatic Chronic 2, H411;  Skin Sens. 1, H317	
CAS: 29964-84-9	isodecyl methacrylate	2.5-10%
EINECS: 249-978-2	Aquatic Acute 1, H400; Aquatic Chronic 1, H410; 🍑 Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
CAS: 75980-60-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphinoxide	≤2.5%
EINECS: 278-355-8	Repr. 2, H361f; Aquatic Chronic 2, H411; Skin Sens. 1, H317	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.

(Contd. on page 3)



Printing date 24.11.2020 Version number 5 Revision: 24.11.2020

Trade name: FotoTec DLP.flex 70 Shore

(Contd. of page 2)

#### After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eve contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Do not induce vomiting.

Call a doctor immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

### **SECTION 6: Accidental release measures**

• 6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

- 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### **SECTION 7: Handling and storage**

#### · 7.1 Precautions for safe handling

Avoid contact with skin and eyes.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

(Contd. on page 4)



Printing date 24.11.2020 Version number 5 Revision: 24.11.2020

Trade name: FotoTec DLP.flex 70 Shore

(Contd. of page 3)

- · Information about fire and explosion protection: Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Protect from heat and direct sunlight.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Do not inhale fumes.

· Protection of hands:



Protective gloves

Protective gloves should be changed regularly, especially after intensive contact with the product. For every workplace a suitable type of protective gloves must be selected.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

#### · Material of gloves

Nitrile rubber, NBR (0,4 mm)

As there are many different conditions in every day work these indications can only serve as an aid to orientation for the selection of suitable gloves for the handling of chemical products. By no means they can replace qualifying examinations by the end-user.

These recommendations only apply to the product mentioned in the safety data sheet. When mixing with other substances or under conditions deviant from norm EN 374 a manufacturer of CE-approved gloves should be referred to.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)



Printing date 24.11.2020 Version number 5 Revision: 24.11.2020

Trade name: FotoTec DLP.flex 70 Shore

(Contd. of page 4)

#### Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

## **SECTION 9: Physical and chemical properties**

<ul> <li>9.1 Information</li> </ul>	n on basi	: physical a	and chemical	properties
-------------------------------------	-----------	--------------	--------------	------------

· General Information

· Appearance:

Form: Fluid

Colour: Clear transparent
Odour: Characteristic
Odour threshold: Not determined.

• pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 149 °C

· Flash point: 100 °C

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 295 °C

• Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined.
Upper: Not determined.
Oxidising properties Not determined Not applicable.

· Vapour pressure: Not determined.

Density at 20 °C:
 Relative density
 Vapour density
 Evaporation rate
 1.06 g/cm³
 Not determined.
 Not determined.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

(Contd. on page 6)



Printing date 24.11.2020 Version number 5 Revision: 24.11.2020

Trade name: FotoTec DLP.flex 70 Shore

(Contd. of page 5)

· Viscosity:

**Dynamic:** Not determined. **Kinematic:** Not determined.

• 9.2 Other information No further relevant information available.

### **SECTION 10: Stability and reactivity**

- 10.1 Reactivity No dangerous reactions if used according to specifications.
- 10.2 Chemical stability Stable if used according to specifications.
- · Thermal decomposition / conditions to be avoided:

Protect from heat and direct sunlight.

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC5	LD/LC50 values relevant for classification:		
10595-0	6-9 2-	ohenoxyethyl methacrylate	
Oral	LD50	5,000 mg/kg (rat)	
	29964-84-9 isodecyl methacrylate		
Oral	LD50	>5,000 mg/kg (rat)	
		>3,000 mg/kg (rabbit)	

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity

Suspected of damaging the unborn child.

- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.

(Contd. on page 7)



Printing date 24.11.2020 Version number 5 Revision: 24.11.2020

Trade name: FotoTec DLP.flex 70 Shore

(Contd. of page 6)

- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

## **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· European waste catalogue		
HP4	Irritant - skin irritation and eye damage	
HP10	Toxic for reproduction	
HP13	Sensitising	
HP14	Ecotoxic	

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

· 14.1 UN-Number · ADR, IMDG, IATA	UN3082
· 14.2 UN proper shipping name · ADR	3082 ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. ((5-ethyl-1, dioxan-5-yl)methyl acrylate, 2-phenoxyeth methacrylate) 3082 UMWELTGEFÄHRDENDER STOFI FLÜSSIG, N.A.G. ((5-ethyl-1,3-dioxan-5-yl)methacrylate, 2-phenoxyethyl methacrylate)
· IMDG	ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. ((5-ethyl-1, dioxan-5-yl)methyl acrylate, 2-phenoxyeth methacrylate), MARINE POLLUTANT
·IATA	ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. ((5-ethyl-1, dioxan-5-yl)methyl acrylate, 2-phenoxyeth methacrylate)

(Contd. on page 8)



Printing date 24.11.2020 Version number 5 Revision: 24.11.2020

Trade name: FotoTec DLP.flex 70 Shore

14.2 Transport horsel slees/sel	(Contd. of page
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
<b>1 1 1 2 2 2 2 3 3 3 3 4 3 3 3 3 3 3 3 3 3 3</b>	
· Class	9 Miscellaneous dangerous substances ar articles.
· Label	9
· 14.4 Packing group · ADR, IMDG, IATA	III
<ul><li>· 14.5 Environmental hazards:</li><li>· Marine pollutant:</li></ul>	Product contains environmentally hazardous substances: (5-ethyl-1,3-dioxan-5-yl)meth acrylate, 2-phenoxyethyl methacrylate Yes
•	Symbol (fish and tree)
<ul><li>Special marking (ADR):</li><li>Special marking (IATA):</li></ul>	Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Miscellaneous dangerous substance and articles.
Danger code (Kemler):	90
· EMS Number: · Stowage Category	F-A,S-F A
<ul> <li>14.7 Transport in bulk according to Ani of Marpol and the IBC Code</li> </ul>	nex II Not applicable.
· Transport/Additional information:	According to special provision no 375 (AD
	chapter 3.3), according to special provision in 969 (IMDG chapter 3.3 in conjunction with IMDG chapter 2.10.2.7) and according to special provision no A197 (IATA chapter 4.4) single respectively inner packagings with a net quantity < 5 I / 5 kg aren't liable to the regulations meaning those don't need to be sent a hazardous goods. Labelling with pictogram GHS09 is not necessary.
· ADR	969 (IMDG chapter 3.3 in conjunction with IMD chapter 2.10.2.7) and according to speci provision no A197 (IATA chapter 4.4) single respectively inner packagings with a net quanti < 5 l / 5 kg aren't liable to the regulation meaning those don't need to be sent a hazardous goods. Labelling with pictogra GHS09 is not necessary.
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	969 (IMDG chapter 3.3 in conjunction with IMD chapter 2.10.2.7) and according to specific provision no A197 (IATA chapter 4.4) single respectively inner packagings with a net quanti < 5 l / 5 kg aren't liable to the regulation meaning those don't need to be sent a hazardous goods. Labelling with pictografic
· Limited quantities (LQ)	969 (IMDG chapter 3.3 in conjunction with IMD chapter 2.10.2.7) and according to speciprovision no A197 (IATA chapter 4.4) single respectively inner packagings with a net quanti < 5 I / 5 kg aren't liable to the regulation meaning those don't need to be sent a hazardous goods. Labelling with pictogram GHS09 is not necessary.  5L  Code: E1  Maximum net quantity per inner packaging: 30 m Maximum net quantity per outer packaging: 100

(Contd. on page 9)



Printing date 24.11.2020 Version number 5 Revision: 24.11.2020

Trade name: FotoTec DLP.flex 70 Shore

	(Contd. of page 8)
· IATA · Remarks:	According to special provision no A197 (IATA chapter 4.4) single -respectively inner packagings with a net quantity < 5 l / < 5 kg aren't liable to the regulations, meaning those don't need to be sent as hazardous goods. Labelling with pictogram GHS09 is not necessary.
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ((5-ETHYL-1,3- DIOXAN-5-YL)METHYL ACRYLATE, 2- PHENOXYETHYL METHACRYLATE), 9, III

### **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E2 Hazardous to the Aquatic Environment
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H361d Suspected of damaging the unborn child.

H361f Suspected of damaging fertility.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

- · Department issuing SDS: Department Research & Development
- · Contact: Dr. Thomas Veit, Lothar Sutor
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

(Contd. on page 10)



Revision: 24.11.2020

Printing date 24.11.2020 Version number 5

Trade name: FotoTec DLP.flex 70 Shore

(Contd. of page 9)

Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1 Repr. 2: Reproductive toxicity – Category 2
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard — Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard — Category 2

· \* Data compared to the previous version altered.