



Product Name: egger LP/W Lacquer

REF: 307030, 30701, 30702

Date of print: 06.05.2021 Date of last alteration: 06.05.2021

egger



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

egger LP/W Lacquer

UFI: V99X-E9HY-P00A-XV0U

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Ligth curing lacquer for use in audiology.

1.3. Details of the supplier of the safety data sheet

Manufacturer/distributor: egger Otoplastik+Labortechnik GmbH

Street/POB-No.: Aybühlweg 59

Postal code/city/country: 87439 Kempten/Germany

Telephone: +49 831 58113-60

Telefax: +49 831 58113-14

Internet: www.egger.online

E-mail: sales@egger.online

1.4. Emergency telephone number: +49 89 19240

Emergency number: Munich, Germany, toxicological dep. of the II. Med. Hospital)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Respiratory or skin sensitisation: Skin Sens. 1

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause respiratory irritation.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

ethyl methacrylate

2-hydroxyethyl methacrylate

hexyl methacrylate

diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

Signal word: Danger

Pictograms:



**Product Name: egger LP/W Lacquer**

REF: 307030, 30701, 30702

Date of print: 06.05.2021 Date of last alteration: 06.05.2021

Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P235 Keep cool.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/ container in accordance with local and national regulations.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Mixture of acrylic/methacrylic resins with auxiliary matters.

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
97-63-2	ethyl methacrylate			30 - < 35 %
	202-597-5	607-071-00-2		
	Flam. Liq. 2, Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3; H225 H315 H319 H317 H335			
868-77-9	2-hydroxyethyl methacrylate			5 - < 10 %
	212-782-2	607-124-00-X		
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1; H315 H319 H317			
142-09-6	hexyl methacrylate			1 - < 5 %
	205-521-9			
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3; H315 H319 H317 H335			
75980-60-8	diphenyl(2, 4, 6-trimethylbenzoyl)phosphine oxide			1 - < 5 %
	278-355-8	015-203-00-X		
	Repr. 2, Skin Sens. 1B, Aquatic Chronic 2; H361f H317 H411			

Full text of H and EUH phrases: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****After inhalation**

Provide fresh air. Medical treatment necessary.

**Product Name: egger LP/W Lacquer**

REF: 307030, 30701, 30702

Date of print: 06.05.2021 Date of last alteration: 06.05.2021


egger**After contact with skin**

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Rinse mouth immediately and drink plenty of water. Seek immediately medical advice. Do not induce vomiting. In case of spontaneous vomiting take care of an unhindered flow out of the vomit (danger of suffocation).

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water spray jet, Carbon dioxide (CO₂), Foam, Extinguishing powder.

5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e. g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13



Product Name: egger LP/W Lacquer

REF: 307030, 30701, 30702

Date of print: 06.05.2021 Date of last alteration: 06.05.2021

egger



SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition. No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

Further information on storage conditions

Keep only in the original container in a cool, dry and well-ventilated place, away from foodstuffs. Keep away from all kind of lighth. An inert gas blanket should not be applied, because the stability of the product depends on the presence of oxygen (air).

7.3. Specific end use(s)

Lacquer for coating of earmoulds. For use by trained specialist staff.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable are gloves of the following material: Butyl caoutchouc (butyl rubber).

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

**Product Name: egger LP/W Lacquer**

REF: 307030, 30701, 30702

Date of print: 06.05.2021 Date of last alteration: 06.05.2021

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state: liquid
 Colour: light blue
 Odour: faintly like esters

		Test method
pH-Value:	not determined	
Changes in the physical state		
Melting point:	not determined	
Initial boiling point and boiling range:	119 - 121 °C	
Flash point:	19 °C	
Flammability		
Solid:	not applicable	
Gas:	not applicable	
Lower explosion limits:	1.4 vol. %	
Upper explosion limits:	not determined	
Ignition temperature:	280 °C	DIN 51794
Auto-ignition temperature		
Solid:	not applicable	
Gas:	not applicable	
Decomposition temperature:	not determined	
Oxidizing properties	not oxidizing	
Vapour pressure (at 20 °C):	20 hPa	
Density (at 20 °C):	1.03 g/cm ³	DIN 51757
Water solubility (at 20 °C):	insoluble	
Solubility in other solvents	not determined	
Partition coefficient:	not determined	
Viscosity / dynamic:	100 mPa·s	Rheostress
Vapour density:	not determined	
Evaporation rate:	not determined	

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity**10.1. Reactivity**

Highly flammable.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Reacts with: oxidising agents, radicals forming substances or heavy metal ions.



Product Name: egger LP/W Lacquer

REF: 307030, 30701, 30702

Date of print: 06.05.2021 Date of last alteration: 06.05.2021

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Ultra-violet light and daylight initiate polymerisation of the product. Therefore keep only in tightly closed containers away from any sources of light. Keep in a refrigerator at 2°C - 25°C / 36°F - 77 °F.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

In case of fire, acrid acrylic fumes may occur.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure routes	Dose	Species	Source	Method
97-63-2	ethyl methacrylate				
	oral	LD50 14800 mg/kg	Rat	GESTIS	
	inhalative (4 h) vapour	LC50 38.7 mg/l	Rat	GESTIS	
868-77-9	2-hydroxyethyl methacrylate				
	oral	LD50 5050 mg/kg	Rat		
	dermal	LD50 >3000 mg/kg	Rabbit		
75980-60-8	diphenyl(2, 4, 6-trimethylbenzoyl)phosphine oxide				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rat		

Irritation and corrosivity

Causes skin irritation. Causes serious eye irritation.

Sensitising effects

May cause an allergic skin reaction. (ethyl methacrylate; 2-hydroxyethyl methacrylate; hexyl methacrylate; diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide).

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (ethyl methacrylate).

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

**Product Name: egger LP/W Lacquer**

REF: 307030, 30701, 30702

Date of print: 06.05.2021 Date of last alteration: 06.05.2021

SECTION 12: Ecological information**12.1. Toxicity**

The product is not: Ecotoxic.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
97-63-2	ethyl methacrylate					
	Acute fish toxicity	LC50 100 mg/l	96 h	Salmo trutta fario (L) (Freshwater trout)	OECD 203	
	Acute algae toxicity	ErC50 >110 mg/l	72 h	Pseudokirchneriella subcapitata	OECD 201	
	Acute crustacea toxicity	EC50 >66 mg/l	48 h	Daphnia magna (Big water flea)		
868-77-9	2-hydroxyethyl methacrylate					
	Acute fish toxicity	LC50 227 mg/l	96 h	Pimephales promelas		
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide					
	Acute algae toxicity	ErC50 >2.01 mg/l	72 h	Scenedesmus subspicatus		
	Acute crustacea toxicity	EC50 3.53 mg/l	48 h	Daphnia magna (Big water flea)		
	Acute bacteria toxicity	(>1000 mg/l)	3 h	Activated sludge		

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
868-77-9	2-hydroxyethyl methacrylate			
	84	%	28	
	Leicht biologisch abbaubar.			
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide			
		0 - 10%	28	
	Not readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
97-63-2	ethyl methacrylate	1.87
868-77-9	2-hydroxyethyl methacrylate	0.47
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	3.1

BCF

CAS No	Chemical name	BCF	Species	Source
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	47-55	Cyprinus carpio (Common Carp)	



Product Name: egger LP/W Lacquer

REF: 307030, 30701, 30702

Date of print: 06.05.2021 Date of last alteration: 06.05.2021

egger



12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

Not identified as PBT/vPvB substances.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1866

14.2. UN proper shipping name: Resin solution

14.3. Transport hazard class(es): 3

14.4. Packing group: II

Hazard label: 3

Classification code: F1

Limited quantity: 5 L/30 kg

Hazard No: 33

Tunnel restriction code: D/E

Other applicable information (land transport)

Flammable liquid

Marine transport (IMDG)

14.1. UN number: UN 1866

14.2. UN proper shipping name: Resin solution

14.3. Transport hazard class(es): 3

14.4. Packing group: II

Hazard label: 3

Marine pollutant: -

Special Provisions: -

Limited quantity: 5L/30 kg

EmS: F-E, S-E

Other applicable information (marine transport)

Flash point: 19 °C c.c.



Product Name: egger LP/W Lacquer

REF: 307030, 30701, 30702

Date of print: 06.05.2021 Date of last alteration: 06.05.2021


egger

Air transport (ICAO)

14.1. UN number: UN 1866

14.2. UN proper shipping name: Resin solution

14.3. Transport hazard class(es): 3

14.4. Packing group: II

Hazard label: 3

Limited quantity Passenger: 1 L/30 kg

Passenger LQ: Y341

Excepted quantity: E2

IATA-packing instructions - Passenger: 353

IATA-max. quantity - Passenger: 5 L

IATA-packing instructions - Cargo: 364

IATA-max. quantity - Cargo: 60 L

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the, juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50 %


LD50: Lethal dose, 50 %



Product Name: egger LP/W Lacquer

REF: 307030, 30701, 30702

Date of print: 06.05.2021 Date of last alteration: 06.05.2021



Relevant H- and EUH-phrases (Number and full text)

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H361f Suspected of damaging fertility.
H411 Toxic to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)