

Printing date 12.01.2021 Version number 5 Revision: 12.01.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: FotoScreen
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Light curing Lacquer
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Dreve Otoplastik GmbH Max-Planck-Straße 31 59423 Unna / Germany Tel.: ++49 2303 / 8807-0 Fax.: ++49 2303 / 8807-29

· Further information obtainable from:

Department Research & Development

Fax: ++49 2303 / 8807-562

Email: sicherheitsdatenblatt@dreve.de

• 1.4 Emergency telephone number:

Tel.: ++ 49 211 / 797-3350 Plant Fire Department Henkel

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

· Signal word Danger

(Contd. on page 2)



Printing date 12.01.2021 Version number 5 Revision: 12.01.2021

Trade name: FotoScreen

(Contd. of page 1)

· Hazard-determining components of labelling:

methyl methacrylate

2-Propenoic acid, reaction products with dipentaerythritol

Neopentylglycol(PO)2 Diacrylate

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse

skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 80-62-6	methyl methacrylate	25-50%	
EINECS: 201-297-1	♦ Flam. Liq. 2, H225; ♦ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335		
CAS: 1384855-91-7	2-Propenoic acid, reaction products with dipentaerythritol	25-50%	
	Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412		
CAS: 41637-38-1	Ethoxylated (04) Bisphenol A Dimethacrylate	2.5-10%	
EC number: 609-946-4	Aquatic Chronic 4, H413		
CAS: 75980-60-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphinoxide	≤2.5%	
EINECS: 278-355-8			
CAS: 84170-74-1	Neopentylglycol(PO)2 Diacrylate	≤2.5%	
EC number: 617-546-6	4 Aquatic Chronic 2, H411; 1 Skin Sens. 1, H317		

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.

(Contd. on page 3)



Printing date 12.01.2021 Version number 5 Revision: 12.01.2021

Trade name: FotoScreen

(Contd. of page 2)

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eve contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Do not induce vomiting.

Call a doctor immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Avoid contact with skin and eyes.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

(Contd. on page 4)



Printing date 12.01.2021 Version number 5 Revision: 12.01.2021

Trade name: FotoScreen

(Contd. of page 3)

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Requirements to be met by storerooms and receptacles:

Protect from heat and direct sunlight.

Store in a cool location.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

80-62-6 methyl methacrylate

WEL Short-term value: 416 mg/m³, 100 ppm

Long-term value: 208 mg/m³, 50 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Respiratory protection:

Do not inhale fumes.

Use suitable respiratory protective device in case of insufficient ventilation.

· Protection of hands:



Protective gloves

Protective gloves should be changed regularly, especially after intensive contact with the product. For every workplace a suitable type of protective gloves must be selected.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Butyl rubber (0,7 mm) EN 374

As there are many different conditions in every day work these indications can only serve as an aid to orientation for the selection of suitable gloves for the handling of chemical products. By no means they can replace qualifying examinations by the end-user.

These recommendations only apply to the product mentioned in the safety data sheet. When mixing with other substances or under conditions deviant from norm EN 374 a manufacturer of CE-approved gloves should be referred to.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)



Printing date 12.01.2021 Version number 5 Revision: 12.01.2021

Trade name: FotoScreen

(Contd. of page 4)

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

 9.1 Information on ba 	sic physical a	and chemical	properties
---	----------------	--------------	------------

· General Information

· Vapour pressure at 20 °C:

· Solubility in / Miscibility with

· Density at 20 °C:

· Relative density

· Vapour density

· Evaporation rate

water:

· Appearance: Form:

Colour: Colourless · Odour: Characteristic · Odour threshold: Not determined. · pH-value: Not determined. · Change in condition Melting point/freezing point: Undetermined. Initial boiling point and boiling range: 101 °C · Flash point: 10 °C · Flammability (solid, gas): Not applicable. · Ignition temperature: 430 °C · Decomposition temperature: Not determined. · Auto-ignition temperature: Product is not selfigniting. · Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible. · Explosion limits: 2.1 Vol % Lower: **Upper:** 12.5 Vol % · Oxidising properties Not determined Not applicable.

47 hPa

1.04 g/cm³

Not determined.

Not determined.

Not determined.

Not miscible or difficult to mix.

Fluid

(Contd. on page 6)

GB



Printing date 12.01.2021 Version number 5 Revision: 12.01.2021

Trade name: FotoScreen

	(Contd. of page
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Solids content:	0.0 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No dangerous reactions if used according to specifications.
- 10.2 Chemical stability Stable if used according to specifications.
- · Thermal decomposition / conditions to be avoided:

Protect from heat and direct sunlight.

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish

(Contd. on page 7)



Printing date 12.01.2021 Version number 5 Revision: 12.01.2021

Trade name: FotoScreen

(Contd. of page 6)

- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage

Disposal must be made according to official regulations.

· European waste catalogue		
HP3	Flammable	
HP4	Irritant - skin irritation and eye damage	
HP5	HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity	
HP13	Sensitising	
HP14	Ecotoxic	

- Uncleaned packaging:
- · **Recommendation:** Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN1247
	OIVIZH
14.2 UN proper shipping name	
ADR	1247 METHYL METHACRYLATE MONOME STABILIZED solution
IMDG, IATA	METHYL METHACRYLATE MONOMEI
	STABILIZED solution
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	II .



Printing date 12.01.2021 Version number 5 Revision: 12.01.2021

Trade name: FotoScreen

	(Contd. of page 7
14.5 Environmental hazards:Marine pollutant:	No
 14.6 Special precautions for user Danger code (Kemler): EMS Number: Stowage Category Stowage Code 	Warning: Flammable liquids. 33 F-E,S-D B SW2 Clear of living quarters.
 14.7 Transport in bulk according to Ann of Marpol and the IBC Code 	Not applicable.
· Transport/Additional information:	
 ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code 	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml 2 D/E
IMDG Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1247 METHYL METHACRYLATE MONOMER, STABILIZED SOLUTION, 3, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

(Contd. on page 9)



Printing date 12.01.2021 Version number 5 Revision: 12.01.2021

Trade name: FotoScreen

(Contd. of page 8)

H335 May cause respiratory irritation.

H361f Suspected of damaging fertility.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

- · Department issuing SDS: Department Research & Development
- · Contact: Dr. Thomas Veit, Lothar Sutor, Susanne Weber
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

- GB