

according to Regulation (EC) No 1907/2006

freeprint® splint 2.0 385

Product code: 1113 Revision date: 17.12.2020 Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

freeprint® splint 2.0 385

UFI: WEX0-Y16M-C007-R22G

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Light curing one component material for the fabrication of dental splints and guides.

1.3. Details of the supplier of the safety data sheet

Company name: DETAX GmbH & Co. KG Street: Carl-Zeiss-Strasse Place: D-76275 Ettlingen Telephone: +49 7243/510-0

Telefax: +49 7243/510-100

e-mail: post@detax.de Internet: www.detax.de Emergency number: Responsible Department: +49 7243/510-0

This number is only obtainable during office hours (Monday - Thursday 8.00 a.m.

- 5.00 p.m., Friday 8.00 a.m. - 4.00 p.m.)

1.4. Emergency telephone +49 7243/510-0

This number is only obtainable during office hours (Monday - Thursday 8.00 a.m. number:

- 5.00 p.m., Friday 8.00 - 4.00 p.m.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eve damage/eve irritation: Eve Irrit. 2 Respiratory or skin sensitisation: Skin Sens. 1A

Specific target organ toxicity - single exposure: STOT SE 3 Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements: Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. May cause respiratory irritation.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

isopropylidenediphenol peg-2 dimethacrylate 2-Propenoic acid, (5-ethyl-1,3-dioxan-5-yl)methyl ester diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

Signal word: Warning

Pictograms:





according to Regulation (EC) No 1907/2006

freeprint® splint 2.0 385

Revision date: 17.12.2020 Product code: 1113 Page 2 of 9

Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/ container in accordance with local and national regulations.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of acrylic/ methacrylic resins with auxilliary matters.

Hazardous components

CAS No	Chemical name					
	EC No	Index No	REACH No			
	GHS Classification					
41637-38-1	isopropylidenediphenol peg-2 dim	isopropylidenediphenol peg-2 dimethacrylate				
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1A, STOT SE 3; H315 H319 H317 H335					
66492-51-1	2-Propenoic acid, (5-ethyl-1,3-dioxan-5-yl)methyl ester					
	266-380-7					
	Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H317 H411					
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide					
	278-355-8	015-203-00-X				
	Repr. 2, Skin Sens. 1B, Aquatic Chronic 2; H361f H317 H411					

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation


Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.





according to Regulation (EC) No 1907/2006

freeprint® splint 2.0 385

Revision date: 17.12.2020 Product code: 1113 Page 3 of 9

After ingestion

Rinse mouth immediately and drink plenty of water.

Seek immediately medical advice. Do not induce vomiting. In case of spontaneous vomiting take care of an unhindered flow out of the vomit (danger of suffocation).

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

5.2. Special hazards arising from the substance or mixture

Non-flammable

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.

Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Hints on joint storage

Keep away from spontaneous flammable or combustible substances.

DETAX GmbH & Co. KG



Safety Data Sheet

according to Regulation (EC) No 1907/2006

freeprint® splint 2.0 385

Revision date: 17.12.2020 Product code: 1113 Page 4 of 9

Further information on storage conditions

Keep only in the original container in a dry and well-ventilated place, away from foodstuffs. Keep away from all kind of ligth. An inert gas blanket should not be applied, because the stability of the product depends on the presence of oxygen (air).

7.3. Specific end use(s)

Ligth curing material for fabrication of dental splints and guides.

For use by trained specialist staff.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable are gloves of the following material: Butyl caoutchouc (butyl rubber)

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid: Colour: blue

Odour: faintly like esters

Test method

pH-Value: not determined

Changes in the physical state

Melting point: not determined Initial boiling point and boiling range: not determined

Flash point: >100 °C DIN 51755

Flammability

Solid: not applicable
Gas: not applicable
Lower explosion limits: not determined

Revision No: 1,02 GB - EN Print date: 18.12.2020

DETAX GmbH & Co. KG



Safety Data Sheet

according to Regulation (EC) No 1907/2006

freeprint® splint 2.0 385

Revision date: 17.12.2020 Product code: 1113 Page 5 of 9

Upper explosion limits: not determined

Auto-ignition temperature

Solid: not applicable
Gas: not applicable

Decomposition temperature: >=190 °C

Oxidizing properties

Not oxidizing.

Vapour pressure: <1 hPa

(at 20 °C)

Density (at 20 °C): 1,09 g/cm³ DIN 51757

Water solubility: insoluble

Solubility in other solvents

not determined

Partition coefficient: not determined Vapour density: not determined Evaporation rate: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Reacts with: strong oxidising agents, strong alcaline or acidic materials.

10.4. Conditions to avoid

Ultra-violet ligth and dayligth initiate polymerisation of the product. Therefore keep only in tigthly closed containers away from any sources of ligth at 15°C - 28°C / 59°F - 82 °F.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

freeprint® splint 2.0 385

Revision date: 17.12.2020 Product code: 1113 Page 6 of 9

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
66492-51-1	2-Propenoic acid, (5-ethy	2-Propenoic acid, (5-ethyl-1,3-dioxan-5-yl)methyl ester				
	oral	LD50 >: mg/kg	2000	Rat		
	dermal	LD50 2 mg/kg	000	Rat		
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide					
	oral	LD50 >: mg/kg	5000	Rat		
	dermal	LD50 >: mg/kg	2000	Rat		

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

May cause an allergic skin reaction. (isopropylidenediphenol peg-2 dimethacrylate; 2-Propenoic acid, (5-ethyl-1,3-dioxan-5-yl)methyl ester; diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (isopropylidenediphenol peg-2 dimethacrylate)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method	
66492-51-1	2-Propenoic acid, (5-ethyl	2-Propenoic acid, (5-ethyl-1,3-dioxan-5-yl)methyl ester						
	Acute fish toxicity	LC50	4 mg/l		Oncorhynchus mykiss (Rainbow trout)			
	Acute algae toxicity	ErC50	34 mg/l		Desmodesmus subspicatus.			
	Acute crustacea toxicity	EC50	20 mg/l		Daphnia magna (Big water flea)			
	Acute bacteria toxicity	(>1,000 n	ng/l)	3 h	Activated sludge			
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide							
	Acute algae toxicity	ErC50 mg/l	>2,01		Scenedesmus subspicatus			
	Acute crustacea toxicity	EC50 mg/l	3,53		Daphnia magna (Big water flea)			
	Acute bacteria toxicity	(>1000 m	ng/l)	3 h	Activated sludge			



according to Regulation (EC) No 1907/2006

freeprint® splint 2.0 385

Revision date: 17.12.2020 Product code: 1113 Page 7 of 9

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
66492-51-1	2-Propenoic acid, (5-ethyl-1,3-dioxan-5-yl)methyl ester				
	Evidence for inherent biodegradability.	28%	28		
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide				
		0-10%	28		
	Not readily biodegradable (according to OECD criteria)				

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
66492-51-1	2-Propenoic acid, (5-ethyl-1,3-dioxan-5-yl)methyl ester	1,9
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	3,1

BCF

CAS No	Chemical name	BCF	Species	Source
	diphenyl(2,4,6-trimethylbenzoyl)phosphi ne oxide	47-55	Cyprinus carpio (Common Carp)	

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

Not identivied as PBT/ vPvB substances

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number: No dangerous good in sense of this transport regulation.



according to Regulation (EC) No 1907/2006

freeprint® splint 2.0 385

Revision date: 17.12.2020 Product code: 1113 Page 8 of 9

14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 3 - strongly hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure			
Skin Irrit. 2; H315	Calculation method			
Eye Irrit. 2; H319	Calculation method			
Skin Sens. 1A; H317	Calculation method			
STOT SE 3; H335	Calculation method			
Aquatic Chronic 3; H412	Calculation method			



according to Regulation (EC) No 1907/2006

freeprint® splint 2.0 385

Revision date: 17.12.2020 Product code: 1113 Page 9 of 9

Relevant H and EUH statements (number and full text)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H361f	Suspected of damaging fertility.

H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)