

according to Regulation (EC) No 1907/2006

# freeprint® model 385

Revision date: 31.05.2021 Product code: 935 Page 1 of 10

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

freeprint® model 385

UFI: AYPY-60YS-400H-E40K; CSKY-G0F2-T006-XGF6; DCPY-P050-0001-SQX4;

S981-51K8-K004-UA2W

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Ligth-curing resin for the generative fabrication of dental models.

1.3. Details of the supplier of the safety data sheet

Company name: DETAX GmbH & Co. KG
Street: Carl-Zeiss-Strasse
Place: D-76275 Ettlingen

Telephone: +49 7243/510-0 Telefax: +49 7243/510-100

e-mail: post@detax.de
Internet: www.detax.de
Responsible Department: Emergency number:
+49 7243/510-0

This number is only obtainable during office hours (Monday - Thursday 8.00 a.m.

- 5.00 p.m., Friday 8.00 a.m. - 4.00 p.m.)

**1.4. Emergency telephone** +49 7243/510-0

number: This number is only obtainable during office hours (Monday - Thursday 8.00 a.m.

- 5.00 p.m., Friday 8.00 - 4.00 p.m.)

#### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

#### Regulation (EC) No. 1272/2008

Hazard categories:

Serious eye damage/eye irritation: Eye Irrit. 2 Respiratory or skin sensitisation: Skin Sens. 1

Reproductive toxicity: Repr. 1B

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Causes serious eye irritation.

May cause an allergic skin reaction.

May damage the unborn child.

Harmful to aquatic life with long lasting effects.

### 2.2. Label elements

### Regulation (EC) No. 1272/2008

# Hazard components for labelling

aliphatic urethane acrylate tripropyleneglycol diacrylate

tetrahydrofurfuryl methacrylate THFMA purified grade diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide

Signal word: Danger

Pictograms:







according to Regulation (EC) No 1907/2006

## freeprint® model 385

Revision date: 31.05.2021 Product code: 935 Page 2 of 10

#### **Hazard statements**

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H360D May damage the unborn child.

H412 Harmful to aquatic life with long lasting effects.

#### **Precautionary statements**

P201 Obtain special instructions before use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P308+P313 IF exposed or concerned: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/ container in accordance with local and national regulations.

#### 2.3. Other hazards

No information available.

### **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

#### **Chemical characterization**

Mixture of acrylic/ methacrylic resins with auxilliary matters.

## **Hazardous components**

CAS No	Chemical name				
	EC No	Index No	REACH No		
	GHS Classification				
	acrylated resin	10 - 40 %			
	Eye Irrit. 2; H319				
	aliphatic urethane acrylate			1 - 15 %	
	906-949-5		01-2120266262-60		
	Skin Sens. 1B, Aquatic Chronic 2;	H317 H411	•		
42978-66-5	tripropyleneglycol diacrylate			1 - 10 %	
	256-032-2		01-2119484613-34		
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. H411	1, STOT SE 3, Aquatic C	Chronic 2; H315 H319 H317 H335		
2455-24-5	tetrahydrofurfuryl methacrylate TH	1 - 15 %			
	219-529-5				
	Repr. 1B, Skin Sens. 1, Aquatic Ch	ronic 3; H360D H317 H4	12		
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)ph	osphine oxide		0,1 - 5 %	
	278-355-8	015-203-00-X			
	Repr. 2, Skin Sens. 1B, Aquatic Ch				
162881-26-7	phenyl bis(2,4,6-trimethylbenzoyl)-	0,1 - 5 %			
	423-340-5	015-189-00-5	01-2119489401-38		
	Skin Sens. 1, Aquatic Chronic 4; H317 H413				

Full text of H and EUH statements: see section 16.

DETAX GmbH & Co. KG



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

## freeprint® model 385

Revision date: 31.05.2021 Product code: 935 Page 3 of 10

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

#### After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

#### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

#### After ingestion

Rinse mouth immediately and drink plenty of water.

Seek immediately medical advice. Do not induce vomiting. In case of spontaneous vomiting take care of an unhindered flow out of the vomit (danger of suffocation).

### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

### Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

## 5.2. Special hazards arising from the substance or mixture

Non-flammable.

### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

### Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.

Do not allow entering drains or surface water.

#### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

#### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

DETAX GmbH & Co. KG



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

## freeprint® model 385

Revision date: 31.05.2021 Product code: 935 Page 4 of 10

#### Advice on safe handling

No special measures are necessary.

#### Advice on protection against fire and explosion

No special fire protection measures are necessary.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed.

#### Hints on joint storage

Keep away from spontaneous flammable or combustible substances.

#### Further information on storage conditions

Keep only in the original container in a dry and well-ventilated place, away from foodstuffs. Keep away from all kind of ligth. An inert gas blanket should not be applied, because the stability of the product depends on the presence of oxygen (air).

#### 7.3. Specific end use(s)

Ligth-curing resin for the generative fabrication of dental models.

For use by trained specialist staff.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### 8.2. Exposure controls

#### Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

#### Eye/face protection

Suitable eye protection: goggles.

#### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable are gloves of the following material: Butyl caoutchouc (butyl rubber)

#### Skin protection

Wear suitable protective clothing.

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state: liquid:

Colour: several shades, according to the product name

Odour: faintly like esters

Test method

pH-Value: not determined

Changes in the physical state

Melting point: not determined

DETAX GmbH & Co. KG



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

freeprint® model 385

Revision date: 31.05.2021 Product code: 935 Page 5 of 10

Initial boiling point and boiling range: not determined

Flash point: >100 °C DIN 51755

**Flammability** 

Solid: not applicable
Gas: not applicable
Lower explosion limits: not determined
Upper explosion limits: not determined

**Auto-ignition temperature** 

Solid: not applicable
Gas: not applicable
Decomposition temperature: >=190 °C

**Oxidizing properties** 

Not oxidizing.

Vapour pressure: <1 hPa

(at 20 °C)

Density (at 20 °C): 1,09 g/cm³ DIN 51757

Water solubility: practically insoluble

Solubility in other solvents

not determined

Partition coefficient: not determined

Vapour density: not determined

Evaporation rate: not determined

9.2. Other information

Solid content: not determined

### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

Reacts with: strong oxidising agents, strong alcaline or acidic materials.

#### 10.4. Conditions to avoid

Ultra-violet ligth and dayligth initiate polymerisation of the product. Therefore keep only in tigthly closed containers away from any sources of ligth at  $15^{\circ}\text{C}$  -  $28^{\circ}\text{C}$  /  $59^{\circ}\text{F}$  -  $82^{\circ}\text{F}$ .

### 10.5. Incompatible materials

No information available.

#### 10.6. Hazardous decomposition products

In case of fire, acrid acrylic fumes may occur.

### **SECTION 11: Toxicological information**

# 11.1. Information on toxicological effects

**Acute toxicity** 



according to Regulation (EC) No 1907/2006

# freeprint® model 385

Revision date: 31.05.2021 Product code: 935 Page 6 of 10

Based on available data, the classification criteria are not met.

For the product itself no toxicological data are available. In products with a comparable composition, a LD50 (orally, species rat) of > 5000 mg/kg has been found.

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
	acrylated resin							
	oral	LD50 mg/kg	>2000	Rat				
	dermal	LD50 mg/kg	>2000	Rabbit				
	aliphatic urethane acryla	te						
	oral	LD50 mg/kg	>5000	Rat	OECD 401			
42978-66-5	tripropyleneglycol diacrylate							
	oral	LD50 mg/kg	6200	Rat				
	dermal	LD50 mg/kg	>2000	Rabbit				
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide							
	oral	LD50 mg/kg	>5000	Rat				
	dermal	LD50 mg/kg	>2000	Rat				
162881-26-7	phenyl bis(2,4,6-trimethy	phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide						
	oral	LD50 mg/kg	>2000	Rat	OECD 401			
	dermal	LD50 mg/kg	>2000	Rat	OECD 402			

## Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

#### Sensitising effects

May cause an allergic skin reaction. (aliphatic urethane acrylate; tripropyleneglycol diacrylate; tetrahydrofurfuryl methacrylate THFMA purified grade; diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide; phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide)

### Carcinogenic/mutagenic/toxic effects for reproduction

May damage the unborn child. (tetrahydrofurfuryl methacrylate THFMA purified grade) Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met.

### STOT-single exposure

Based on available data, the classification criteria are not met.

# STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

### Additional information on tests

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

# **SECTION 12: Ecological information**

## 12.1. Toxicity



according to Regulation (EC) No 1907/2006

# freeprint® model 385

Revision date: 31.05.2021 Product code: 935 Page 7 of 10

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method	
	aliphatic urethane acrylate							
	Acute algae toxicity	ErC50 mg/l	>0,68	72 h	(algae)	OECD 201		
	Acute crustacea toxicity	EC50 mg/l	>1,2	48 h	(daphnia)	OECD 202		
42978-66-5	tripropyleneglycol diacryla	ate						
	Acute fish toxicity	LC50 mg/l	4,5-10	96 h	Leuciscus idus (golden orfe)			
	Acute algae toxicity	ErC50	>28 mg/l	72 h	Desmodesmus subspicatus.			
	Acute crustacea toxicity	EC50 mg/l	88,7	48 h	Daphnia magna (Big water flea)			
2455-24-5	tetrahydrofurfuryl methacrylate THFMA purified grade							
	Acute fish toxicity	LC50 mg/l	34,7	96 h				
	Acute algae toxicity	ErC50 mg/l	>100	72 h				
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide							
	Acute algae toxicity	ErC50 mg/l	>2,01	72 h	Scenedesmus subspicatus			
	Acute crustacea toxicity	EC50 mg/l	3,53	48 h	Daphnia magna (Big water flea)			
	Acute bacteria toxicity	(>1000 n	ng/l)	3 h	Activated sludge			
162881-26-7	phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide							
	Acute fish toxicity	LC50 mg/l	>0,09	96 h	Brachydanio rerio (zebra-fish)	OECD 203		
	Acute algae toxicity	ErC50 mg/l	>0,26	72 h	Desmodesmus subspicatus.	OECD 201		
	Acute crustacea toxicity	EC50 mg/l	>1,175	48 h	Daphnia magna (Big water flea)	OECD 202		
	Crustacea toxicity	NOEC mg/l	>0,008	21 d	Daphnia magna (Big water flea)	OECD 211		
	Acute bacteria toxicity	(>100 m	g/l)	3 h	OECD 209			

### 12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
	aliphatic urethane acrylate				
	OECD 301B	22%	28		
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide				
		0-10%	28		
	Not readily biodegradable (according to OECD criteria)				
162881-26-7	phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide				
	CO2 formation (% of the theoretical value).	1%	29		
	Not readily biodegradable (according to OECD criteria)				

# 12.3. Bioaccumulative potential



according to Regulation (EC) No 1907/2006

# freeprint® model 385

Revision date: 31.05.2021 Product code: 935 Page 8 of 10

The product has not been tested.

### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	3,1
162881-26-7	phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide	5,8

#### **BCF**

CAS No	Chemical name	BCF	Species	Source
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphi ne oxide	47-55	Cyprinus carpio (Common Carp)	
162881-26-7	phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide	<5	Cyprinus carpio (Common Carp)	OECD 305

#### 12.4. Mobility in soil

The product has not been tested.

#### 12.5. Results of PBT and vPvB assessment

Not identivied as PBT/ vPvB substances

### 12.6. Other adverse effects

No information available.

#### Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

# **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

# **Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

#### Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

# **SECTION 14: Transport information**

## Land transport (ADR/RID)

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

### Inland waterways transport (ADN)

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

### Marine transport (IMDG)

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.



according to Regulation (EC) No 1907/2006

## freeprint® model 385

Revision date: 31.05.2021 Product code: 935 Page 9 of 10

### Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

#### 14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No dangerous good in sense of this transport regulation.

### **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 3 - strongly hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

#### **SECTION 16: Other information**

#### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

# Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Repr. 1B; H360D	Calculation method
Aquatic Chronic 3; H412	Calculation method

#### Relevant H and EUH statements (number and full text)

H315	Causes skin imitation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H360D	May damage the unborn child.
H361f	Suspected of damaging fertility.

Causas akin irritation

H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.
 H413 May cause long lasting harmful effects to aquatic life.





according to Regulation (EC) No 1907/2006

# freeprint® model 385

Revision date: 31.05.2021 Product code: 935 Page 10 of 10

#### **Further Information**

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)