Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY *(As Used on Label and List)* SOFT ADCO ADDON THINNER Codes 2153

Section I

Manufacturer's Name
ADCO Hearing Products, Inc.

Address *(Number, Street, City, State, and ZIP Code)*
4242 South Broadway
Englewood, CO 80113

Telephone Number for Information
(303)794-3928

Date Prepared
April 15, 2014

Signature of Preparer *(optional)*

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% *(optional)*
2-Propanol(Isopropyl Alcohol, Isopropanol)	400 ppm 980 mg/m3			

Section III — Physical/Chemical Characteristics

Boiling Point	83°C 181°F	Specific Gravity (H_2O = 1)	0.78
Vapor Pressure (mm Hg.)	33	Melting Point	-89°C -128°F
Vapor Density (AIR = 1)	2.1	Evaporation Rate (Butyl Acetate = 1)	2.83

Solubility in Water
Complete(in all proportions)

Appearance and Odor
Colorless, transparent liquid

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used)	Flammable Limits	LEL	UEL
12°C(53°F) Closed cup		2.0%	12.7%

Extinguishing Media
Alcohol Foam, dry chemical, carbon dioxide

Special Fire Fighting Procedures Firefighters should wear proper protective equipment & self-contained breathing apparatus with full facepiece operated in positive pressure mode. Move container from fire area if can be done without risk.

Unusual Fire and Explosion Hazards Vapors may flow along surface to distant ignition source & flash back. Contact with strong oxidizers may cause fire.